

## **TIKKURILA PROFESSIONAL FINNGARD OPAQUE OVER EXISTING PAINTED FACADES.**

Treat all areas affected of algae growth and mould spore growth with Tikkurila Professional Mould Removal mixing ratio of 1 part solution to 4 parts water working from the bottom up to avoid streaks. Allow at least ½ hour for the solution to act and wash down thoroughly with water. REFER TO THE DATA SHEET FOR SAFETY INFORMATION ON THIS PRODUCT.

Remove dirt, oil and grease etc, by washing down with Tikkurila Professional Cleaning Agent using a pressure washer then rinse with clean water and allow to dry thoroughly.

Any surface cracks or damage, must be repaired using a good quality masonry filler and allow to dry thoroughly. Sand to a flat finish prior to painting.

Apply Tikkurila Professional Finngard Primer S to all areas where the paint has been removed or cracks have appeared. Apply to all previously unpainted or repaired render / concrete.

Apply 2-3 coats of the primer using wet-on-wet method of application with e.g. approx. 10 minutes between coats. The number of coats to be applied will depend upon porosity, absorption and condition of the substrate. Finngard Primer S normally requires no thinning, however on hard and less absorbent surfaces it may be thinned by up to 50% with White Spirit.

Apply 2 coats of Tikkurila Professional Finngard Opaque over all prepared areas using good quality roller and synthetic brush (Wooster is recommended), Thin up to a maximum of 5% if required.

**Selected Colour:   RAL 1013 on Facades  
                          BS 00 E 55 on ceilings**

